

Apartment building in Albertslund, DK

PROJECT SUMMARY

14 apartment houses, in total 631 flats, were renovated in the period from 2007-2009. The renovation of the facade respects the original architecture and uses environmentally benign materials.

SPECIAL FEATURES

Renovation of the building envelope incl. mounting of balconies and merging of small apartments into larger family flats.

ARCHITECT

Nova5 Architects, DK

ENERGY CONSULTANT

Niras Consulting Engineers, DK

OWNER

Bo-Vest, DK on behalf of Albertslund Housing Company and Vridsløselille Housing Co-operative.



IEA – SHC Task 37

Advanced Housing Renovation with Solar & Conservation

Before



After

BACKGROUND


The 14 buildings with 631 apartments were built in 1966-69. Since then they have had technical problems primarily with the building envelope. Also the units were depreciated due to the large number of small apartments, occupied for short periods and resulting in a frequent transit of people. Therefore, it was decided to make a comprehensive renovation.

AIMS


Renovate the facade respecting the architecture by using dark Spanish slate. To give the units identity and variety new balconies were added. Residents were involved during the planning.

SUMMARY OF THE RENOVATION

- Merging of flats, making flats suitable for families, elderly and physically disabled people.
- Focusing on daylight and functionality in the new design of the apartment.
- Renovation and adding insulation of facades
- Mounting balconies and gardens
- Common room for social purposes
- Exchange of water pipes and installation of water meters
- New entrances
- New doors and windows in wood/aluminium



Vertical cross section




Plan



After


After



Before

Photos: NOVA5

Before



IMPROVED PLANS

As part of the renovation small flats were merged into larger flats to improve the living quality and better meet demand.


New flats were designed for elderly people (plans to the right).

Each flat was supplied with a separate kitchen, large bathroom and sliding double doors to admit more light into the room.

The flats benefit from new balconies, in contrast to the former French windows.

See the next page for photos.

After



Before



After



DOORS AND DOOR OPENINGS – allowing the light to flow across the rooms





Spanish nature slate is used in the renovation in order to respect the original architecture.


CONSTRUCTION

Floor

U-value: 0.14 W/(m²·K)

(top down)

| | |
|---------------------------------|---------------|
| White oiled parquet (on joists) | 22 mm |
| Vapour barrier with felt | |
| Concrete (with floor heating) | 100 mm |
| Rigid insulation (mineral wool) | 200 mm |
| Capillary break layer | 250 mm |
| Total | 572 mm |




Wall

U-value: 0.19 W/(m²·K)

(interior to exterior)

| | |
|------------------------|---------------|
| Existing concrete wall | 60 mm |
| Tolerance | 12 mm |
| Concrete chipboard, | 8 mm |
| Insulation/ridge | 220 mm |
| Distance list | 16 mm |
| Horizontal laths | 38 mm |
| Nature slate | 14 mm |
| Total | 368 mm |




Roof

U-value: 0.19 W/(m²·K)

(inside towards attic)

| | |
|-----------------------------|---------------|
| Concrete slab | 215 mm |
| Insulation | 75 mm |
| Plywood | 15 mm |
| Roofing felt | 36 mm |
| Insulation | 100 mm |
| Total | 441 mm |
| + attic and asphalt roofing | |





Summary of U-values W/(m²·K)

| | Before | After |
|-----------|--------|-------|
| Roof* | 0.19 | 0.19 |
| Walls | 0.36 | 0.19 |
| Floor | 0.52 | 0.14 |
| Windows** | 3.1 | 1.5 |

*Because the roof was renovated earlier it was not part of this renovation so U-values before and after are the same.

**The U-value is an average for both windows, glass doors and balcony doors

BUILDING SERVICES

District heating as heating supply. Mechanical ventilation in kitchen and bathroom according to Danish building regulations. Manually operated natural ventilation.

The common rooms have mechanical ventilation with rotating heat exchanger and heating surface.

RENEWABLE ENERGY USE

No use of renewable energy

ENERGY PERFORMANCE

Total transmission loss (primary energy)*

Before: 115.6 kWh/m²
 After: 99 kWh/m²
 Reduction: 14% (40%)

Because of a previous renovation of the roof the energy performance “before” was relatively good and therefore the reduction is not as significant as expected. It was not cost effective to insulate the roof construction further and therefore the U-value is not as low as could be expected. However, if the “before” is calculated based on original construction, 50 mm roof insulation and a new roof were insulated to 0.08 W/m²K the reduction would have increased to approximately 40%.

*Conversion factor used for district heating: 0.77 based on 70% CHP-coal and 30% oil.

INFORMATION SOURCES

Building Association BoVest - www.bo-vest.dk
 Nova5 architects - www.nova5.dk
 Niras Consulting Engineers - www.niras.dk

Photos

All photos by NOVA5

Brochure authors

err@esbensen.dk